



Article	H/h, inch	Weight lb	H/h, mm	Weight kg	Article	H/h, inch	Weight lb	H/h, mm	Weight kg	Article	H/h, inch	Weight lb	H/h, mm	Weight kg
0450715509/360	14,2	242,5	360	110,2	0450715509/360-355	14,2/14	241,6	360/355	109,8	0450715509/360-350	14,2/13,8	240,7	360/350	109,4
0450715509/355	14,0	240,9	355	109,5	0450715509/355-350	14/13,8	240,0	355/350	109,1	0450715509/350-340	13,8/13,4	237,6	350/340	108,0
0450715509/350	13,8	239,3	350	108,8	0450715509/350-345	13,8/13,6	238,5	350/345	108,4	0450715509/340-330	13,4/13	234,5	340/330	106,6
0450715509/345	13,6	237,7	345	108,1	0450715509/345-340	13,6/13,4	236,9	345/340	107,7	0450715509/330-320	13/12,6	231,2	330/320	105,1
0450715509/340	13,4	236,1	340	107,3	0450715509/340-335	13,4/13,2	235,3	340/335	107,0	0450715509/320-310	12,6/12,2	228,1	320/310	103,7
0450715509/335	13,2	234,5	335	106,6	0450715509/335-330	13,2/13	233,7	335/330	106,2	0450715509/310-300	12,2/11,8	224,8	310/300	102,2
0450715509/330	13,0	233,0	330	105,9	0450715509/330-325	13/12,8	232,1	330/325	105,5	0450715509/300-290	11,8/11,4	221,8	300/290	100,8
0450715509/325	12,8	231,4	325	105,2	0450715509/325-320	12,8/12,6	230,5	325/320	104,8	0450715509/290-280	11,4/11	218,7	290/280	99,4
0450715509/320	12,6	229,8	320	104,5	0450715509/320-315	12,6/12,4	229,0	320/315	104,1	0450715509/280-270	11/10,6	215,4	280/270	97,9
0450715509/315	12,4	228,2	315	103,7	0450715509/315-310	12,4/12,2	227,4	315/310	103,4	0450715509/270-260	10,6/10,2	212,3	270/260	96,5
0450715509/310	12,2	226,6	310	103,0	0450715509/310-305	12,2/12	225,8	310/305	102,6	0450715509/260-250	10,2/9,8	209,0	260/250	95,0
0450715509/305	12,0	225,0	305	102,3	0450715509/305-300	12/11,8	224,2	305/300	101,9	0450715509/250-240	9,8/9,4	205,9	250/240	93,6
0450715509/300	11,8	223,5	300	101,6	0450715509/300-295	11,8/11,6	222,6	300/295	101,2	0450715509/240-230	9,4/9,1	202,8	240/230	92,2
0450715509/295	11,6	221,9	295	100,9	0450715509/295-290	11,6/11,4	221,0	295/290	100,5	0450715509/230-220	9,1/9,7	199,5	230/220	90,7
0450715509/290	11,4	220,3	290	100,1	0450715509/290-285	11,4/11,2	219,5	290/285	99,8	0450715509/220-210	9,7/8,3	196,5	220/210	89,3
0450715509/285	11,2	218,7	285	99,4	0450715509/285-280	11,2/11	217,9	285/280	99,0	0450715509/210-200	8,3/7,9	193,2	210/200	87,8
0450715509/280	11,0	217,1	280	98,7	0450715509/280-275	11/10,8	216,3	280/275	98,3					
0450715509/275	10,8	215,5	275	98,0	0450715509/275-270	10,8/10,6	214,7	275/270	97,6					
0450715509/270	10,6	214,0	270	97,3	0450715509/270-265	10,6/10,4	213,1	270/265	96,9					
0450715509/265	10,4	212,4	265	96,5	0450715509/265-260	10,4/10,2	211,5	265/260	96,2					
0450715509/260	10,2	210,8	260	95,8	0450715509/260-255	10,2/10	209,9	260/255	95,4					
0450715509/255	10,0	209,2	255	95,1	0450715509/255-250	10/9,8	208,4	255/250	94,7					
0450715509/250	9,8	207,6	250	94,4	0450715509/250-245	9,8/9,6	206,8	250/245	94,0					
0450715509/245	9,6	206,0	245	93,7	0450715509/245-240	9,6/9,4	205,2	245/240	93,3					
0450715509/240	9,4	204,4	240	92,9	0450715509/240-235	9,4/9,3	203,6	240/235	92,6					
0450715509/235	9,3	202,9	235	92,2	0450715509/235-230	9,3/9,1	202,0	235/230	91,8					
0450715509/230	9,1	201,3	230	91,5	0450715509/230-225	9,1/8,9	200,4	230/225	91,1					
0450715509/225	8,9	199,7	225	90,8	0450715509/225-220	8,9/8,7	198,9	225/220	90,4					
0450715509/220	8,7	198,1	220	90,1	0450715509/220-215	8,7/8,5	197,3	220/215	89,7					
0450715509/215	8,5	196,5	215	89,3	0450715509/215-210	8,5/8,3	195,7	215/210	89,0					
0450715509/210	8,3	194,9	210	88,6	0450715509/210-205	8,3/8,1	194,1	210/205	88,2					
0450715509/205	8,1	193,4	205	87,9	0450715509/205-200	8,1/7,9	192,5	205/200	87,5					
0450715509/200	7,9	191,8	200	87,2										

- Dimensions for reference, inch [mm]
- Delivery and packaging are carried out in accordance with the terms of the contract
- The manufacturer reserves the right, without notice to the consumer, to make changes to the design of the products for improvement of their technological and operational parameters, which will not affect the quality and properties of the product
- Deviation of the actual weight of the nominal can be up to 10%.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: ISO 2768 - C LINEAR: ANGULAR:		FINISH:	DEBURR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING	REVISION
DRAWN: Kyselytsia			SIGNATURE:	<p>TITLE: 8'' [DN200] Concrete Drain Channel Pro H7.9''-14.2'' [H200-360] vertical outlet 7.9'' [200] with Cast Iron Grate E600</p>	
CHK'D: Kharambura			DATE: 22.07.22		
APPV'D: Malynovskiy					
MFG:					
QA:					
MATERIAL: Concrete, Cast Iron			ARTICLE:	A3	
WEIGHT: lb / kg			SCALE: 1:7	SHEET 1 OF 1	