





Channel with slotted Grate E600

Channel with slotted Grate E600 and vertical outlet 110



Article	H/h, mm	Weight, kg
04007155/230	230	57,1
04007155/225	225	56,4
04007155/220	220	55,7
04007155/215	215	55,0
04007155/210	210	54,3
04007155/205	205	53,7
04007155/200	200	53,0
04007155/195	195	52,3
04007155/190	190	51,6
04007155/185	185	50,9
04007155/180	180	50,3
04007155/175	175	49,6
04007155/170	170	48,9
04007155/165	165	48,2
04007155/160	160	47,5
04007155/155	155	46,9
04007155/150	150	46,2
04007155/145	145	45,5
04007155/140	140	44,8
04007155/135	135	44,1
04007155/130	130	43,5
04007155/125	125	42,8
04007155/120	120	42,1

Article	H/h, mm	Weight, kg
04007155/230-225	230/225	56,2
04007155/225-220	225/220	55,6
04007155/220-215	220/215	54,9
04007155/215-210	215/210	54,2
04007155/210-205	210/205	53,5
04007155/205-200	205/200	52,8
04007155/200-195	200/195	52,2
04007155/195-190	195/190	51,5
04007155/190-185	190/185	50,8
04007155/185-180	185/180	50,1
04007155/180-175	180/175	49,4
04007155/175-170	175/170	48,8
04007155/170-165	170/165	48,1
04007155/165-160	165/160	47,4
04007155/160-155	160/155	46,7
04007155/155-150	155/150	46,0
04007155/150-145	150/145	45,4
04007155/145-140	145/140	44,7
04007155/140-135	140/135	44,0
04007155/135-130	135/130	43,3
04007155/130-125	130/125	42,6
04007155/125-120	125/120	42,0

Article	H/h, mm	Weight, kg
0400715509/230	230	56,0
0400715509/225	225	55,4
0400715509/220	220	54,7
0400715509/215	215	54,0
0400715509/210	210	53,3
0400715509/205	205	52,6
0400715509/200	200	52,0
0400715509/195	195	51,3
0400715509/190	190	50,6
0400715509/185	185	49,9
0400715509/180	180	49,2
0400715509/175	175	48,6
0400715509/170	170	47,9
0400715509/165	165	47,2
0400715509/160	160	46,5
0400715509/155	155	45,8
0400715509/150	150	45,2
0400715509/145	145	44,5
0400715509/140	140	43,8
0400715509/135	135	43,1
0400715509/130	130	42,4
0400715509/125	125	41,8
0400715509/120	120	41,1

Article	H/h, mm	Weight, kg
0400715509/230-225	230/225	55,2
0400715509/225-220	225/220	54,6
0400715509/220-215	220/215	53,9
0400715509/215-210	215/210	53,2
0400715509/210-205	210/205	52,5
0400715509/205-200	205/200	51,8
0400715509/200-195	200/195	51,2
0400715509/195-190	195/190	50,5
0400715509/190-185	190/185	49,8
0400715509/185-180	185/180	49,1
0400715509/180-175	180/175	48,4
0400715509/175-170	175/170	47,8
0400715509/170-165	170/165	47,1
0400715509/165-160	165/160	46,4
0400715509/160-155	160/155	45,7
0400715509/155-150	155/150	45,0
0400715509/150-145	150/145	44,4
0400715509/145-140	145/140	43,7
0400715509/140-135	140/135	43,0
0400715509/135-130	135/130	42,3
0400715509/130-125	130/125	41,6
0400715509/125-120	125/120	41,0

1. Dimensions for reference
2. Delivery and packaging are carried out in accordance with the terms of the contract
3. The manufacturer reserves the right, without notice to the consumer, to make changes to the design of the products for improvement of their technological and operational parameters, which will not affect the quality and properties of the product
4. Deviation of the actual weight of the nominal can be up to 10%.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS		FINISH:		DEBURR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION	
SURFACE FINISH:								Concrete Drain Channel Pro DN100 H120-230 with Cast Iron Grate E600	
TOLERANCES: ISO 2768 - C									
LINEAR:									
ANGULAR:									
DRAWN: Olender		SIGNATURE:		DATE: 26.06.23					
CHK'D: Kyselytsia									
APPV'D: Malymovskiy									
MFG:									
QA:						MATERIAL: Concrete, Cast Iron			
						WEIGHT: kg		SCALE:1:5	
								SHEET 1 OF 1	