



Article	H/h, inch	Weight lb	H/h, mm	Weight kg
0420715509/310	12,2	189,8	310	86,3
0420715509/305	12,0	188,3	305	85,6
0420715509/300	11,8	186,8	300	84,9
0420715509/295	11,6	185,2	295	84,2
0420715509/290	11,4	183,7	290	83,5
0420715509/285	11,2	182,2	285	82,8
0420715509/280	11,0	180,7	280	82,1
0420715509/275	10,8	179,2	275	81,4
0420715509/270	10,6	177,7	270	80,8
0420715509/265	10,4	176,1	265	80,1
0420715509/260	10,2	174,6	260	79,4
0420715509/255	10,0	173,1	255	78,7
0420715509/250	9,8	171,6	250	78,0
0420715509/245	9,6	170,1	245	77,3
0420715509/240	9,4	168,5	240	76,6
0420715509/235	9,3	167,0	235	75,9
0420715509/230	9,1	165,5	230	75,2
0420715509/225	8,9	164,0	225	74,5
0420715509/220	8,7	162,5	220	73,9
0420715509/215	8,5	161,0	215	73,2
0420715509/210	8,3	159,4	210	72,5
0420715509/205	8,1	157,9	205	71,8
0420715509/200	7,9	156,4	200	71,1
0420715509/195	7,7	154,9	195	70,4
0420715509/190	7,5	153,4	190	69,7
0420715509/185	7,3	151,8	185	69,0
0420715509/180	7,1	150,3	180	68,3
0420715509/175	6,9	148,8	175	67,6
0420715509/170	6,7	147,3	170	67,0
0420715509/165	6,5	145,8	165	66,3
0420715509/160	6,3	144,3	160	65,6
0420715509/155	6,1	142,7	155	64,9

Article	H/h, inch	Weight lb	H/h, mm	Weight kg
0420715509/310-305	12,2/12	189,0	310/305	85,9
0420715509/305-300	12/11,8	187,4	305/300	85,2
0420715509/300-295	11,8/11,6	185,9	300/295	84,5
0420715509/295-290	11,6/11,4	184,4	295/290	83,8
0420715509/290-285	11,4/11,2	182,9	290/285	83,1
0420715509/285-280	11,2/11	181,4	285/280	82,4
0420715509/280-275	11/10,8	179,9	280/275	81,8
0420715509/275-270	10,8/10,6	178,3	275/270	81,1
0420715509/270-265	10,6/10,4	176,8	270/265	80,4
0420715509/265-260	10,4/10,2	175,3	265/260	79,7
0420715509/260-255	10,2/10	173,8	260/255	79,0
0420715509/255-250	10/9,8	172,3	255/250	78,3
0420715509/250-245	9,8/9,6	170,7	250/245	77,6
0420715509/245-240	9,6/9,4	169,2	245/240	76,9
0420715509/240-235	9,4/9,3	167,7	240/235	76,2
0420715509/235-230	9,3/9,1	166,2	235/230	75,5
0420715509/230-225	9,1/8,9	164,7	230/225	74,9
0420715509/225-220	8,9/8,7	163,2	225/220	74,2
0420715509/220-215	8,7/8,5	161,6	220/215	73,5
0420715509/215-210	8,5/8,3	160,1	215/210	72,8
0420715509/210-205	8,3/8,1	158,6	210/205	72,1
0420715509/205-200	8,1/7,9	157,1	205/200	71,4
0420715509/200-195	7,9/7,7	155,6	200/195	70,7
0420715509/195-190	7,7/7,5	154,0	195/190	70,0
0420715509/190-185	7,5/7,3	152,5	190/185	69,3
0420715509/185-180	7,3/7,1	151,0	185/180	68,6
0420715509/180-175	7,1/6,9	149,5	180/175	68,0
0420715509/175-170	6,9/6,7	148,0	175/170	67,3
0420715509/170-165	6,7/6,5	146,5	170/165	66,6
0420715509/165-160	6,5/6,3	144,9	165/160	65,9
0420715509/160-155	6,3/6,1	143,4	160/155	65,2
0420715509/155-150	6,1/5,9	141,9	155/150	64,5

Article	H/h, inch	Weight lb	H/h, mm	Weight kg
0420715509/310-300	12,2/11,8	188,1	310/300	85,5
0420715509/300-290	11,8/11,4	185,0	300/290	84,1
0420715509/290-280	11,4/11,0	181,9	290/280	82,7
0420715509/280-270	11,0/10,6	179,1	280/270	81,4
0420715509/270-260	10,6/10,2	176,0	270/260	80,0
0420715509/260-250	10,2/9,8	172,9	260/250	78,6
0420715509/250-240	9,8/9,4	169,8	250/240	77,2
0420715509/240-230	9,4/9,1	166,8	240/230	75,8
0420715509/230-220	9,1/8,7	163,9	230/220	74,5
0420715509/220-210	8,7/8,3	160,8	220/210	73,1
0420715509/210-200	8,3/7,9	157,7	210/200	71,7
0420715509/200-190	7,9/7,5	154,7	200/190	70,3
0420715509/190-180	7,5/7,1	151,6	190/180	68,9
0420715509/180-170	7,1/6,7	148,7	180/170	67,6
0420715509/170-160	6,7/6,3	145,6	170/160	66,2
0420715509/160-150	6,3/5,9	142,6	160/150	64,8

- Dimensions for reference, inch [mm]
- Delivery and packaging are carried out in accordance with the terms of the contract
- The manufacturer reserves the right, without notice to the consumer, to make changes to the design of the products for improvement of their technological and operational parameters, which will not affect the quality and properties of the product
- Deviation of the actual weight of the nominal can be up to 10%.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: ISO 2768 - C LINEAR: ANGULAR:		FINISH:	DEBURR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING	REVISION
DRAWN: Kyselytsia			SIGNATURE:		
CHK'D: Kharambura			DATE: 22.07.22		
APPV'D: Malynovskiy					
MFG:					
QA:			MATERIAL: Concrete, Cast Iron	ARTICLE:	A3
			WEIGHT: lb / kg	SCALE: 1:5	SHEET 1 OF 1

TITLE:
6'' [DN150] Concrete Drain Channel Pro
H6.1''-12.2'' [H155-310] vertical outlet
4.3'' [110] with Cast Iron Grate E600