



Article	H/h, inch	Weight lb	H/h, mm	Weight kg
04501/335	13,2	284,6	335	129,1
04501/330	13,0	282,6	330	128,2
04501/325	12,8	280,6	325	127,3
04501/320	12,6	278,9	320	126,5
04501/315	12,4	276,9	315	125,6
04501/310	12,2	274,9	310	124,7
04501/305	12,0	272,9	305	123,8
04501/300	11,8	270,9	300	122,9
04501/295	11,6	269,2	295	122,1
04501/290	11,4	267,2	290	121,2
04501/285	11,2	265,2	285	120,3
04501/280	11,0	263,2	280	119,4
04501/275	10,8	261,2	275	118,5
04501/270	10,6	259,5	270	117,7
04501/265	10,4	257,5	265	116,8
04501/260	10,2	255,5	260	115,9
04501/255	10,0	253,5	255	115,0
04501/250	9,8	251,5	250	114,1
04501/245	9,6	249,8	245	113,3
04501/240	9,4	247,8	240	112,4
04501/235	9,3	245,8	235	111,5
04501/230	9,1	243,8	230	110,6
04501/225	8,9	241,8	225	109,7
04501/220	8,7	240,1	220	108,9
04501/215	8,5	238,1	215	108,0

Article	H/h, inch	Weight lb	H/h, mm	Weight kg
04501/335-330	13,2/13,0	283,5	335/330	128,6
04501/330-325	13,0/12,8	281,5	330/325	127,7
04501/325-320	12,8/12,6	279,5	325/320	126,8
04501/320-315	12,6/12,4	277,8	320/315	126,0
04501/315-310	12,4/12,2	275,8	315/310	125,1
04501/310-305	12,2/12,0	273,8	310/305	124,2
04501/305-300	12,0/11,8	271,8	305/300	123,3
04501/300-295	11,8/11,6	269,8	300/295	122,4
04501/295-290	11,6/11,4	268,1	295/290	121,6
04501/290-285	11,4/11,2	266,1	290/285	120,7
04501/285-280	11,2/11,0	264,1	285/280	119,8
04501/280-275	11,0/10,8	262,1	280/275	118,9
04501/275-270	10,8/10,6	260,1	275/270	118,0
04501/270-265	10,6/10,4	258,4	270/265	117,2
04501/265-260	10,4/10,2	256,4	265/260	116,3
04501/260-255	10,2/10,0	254,4	260/255	115,4
04501/255-250	10,0/9,8	252,4	255/250	114,5
04501/250-245	9,8/9,6	250,4	250/245	113,6
04501/245-240	9,6/9,4	248,7	245/240	112,8
04501/240-235	9,4/9,3	246,7	240/235	111,9
04501/235-230	9,3/9,1	244,7	235/230	111,0
04501/230-225	9,1/8,9	242,7	230/225	110,1
04501/225-220	8,9/8,7	240,7	225/220	109,2
04501/220-215	8,7/8,5	239,0	220/215	108,4

Article	H/h, inch	Weight lb	H/h, mm	Weight kg
04501/335-325	13,2/12,8	283,5	335/325	128,6
04501/325-315	12,8/12,4	279,5	325/315	126,8
04501/315-305	12,4/12,0	275,8	315/305	125,1
04501/305-295	12,0/11,6	271,8	305/295	123,3
04501/295-285	11,6/11,2	268,1	295/285	121,6
04501/285-275	11,2/10,8	264,1	285/275	119,8
04501/275-265	10,8/10,4	260,1	275/265	118,0
04501/265-255	10,4/10,0	256,4	265/255	116,3
04501/255-245	10,0/9,6	252,4	255/245	114,5
04501/245-235	9,6/9,3	248,7	245/235	112,8
04501/235-225	9,3/8,9	244,7	235/225	111,0
04501/225-215	8,9/8,5	240,7	225/215	109,2

1. Dimensions for reference, inch [mm]
2. Delivery and packaging are carried out in accordance with the terms of the contract
3. The manufacturer reserves the right, without notice to the consumer, to make changes to the design of the products for improvement of their technological and operational parameters, which will not affect the quality and properties of the product
4. Deviation of the actual weight of the nominal can be up to 10%.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: ISO 2768 - C LINEAR: ANGULAR:		FINISH:	DEBURR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING	REVISION	A-01
DRAWN O. Kozhukh 27.09.2022			TITLE: 8"[DN200] Concrete Drain Channel Mega H13.2"8.5"[H335-215] with Cast Iron Grate F900			
CHK'D V. Kyselytsia	SIGNATURE	DATE	ARTICLE: A3			
APPV'D I. Malynovskiy	MATERIAL: Concrete, Cast Iron		SCALE: 1:10			
MFG	WEIGHT: lb / kg		SHEET 1 OF 1			
QA						